

401752

Sensors

Alwen PIR Batten Mount Sensor













Alwen PIR Batten Mount Sensor



General Data

| Technology | PIR IR |
|--------------------------------|---------------------------------------|
| Electrical Connector Type | Flying Lead |
| Input Electrical Connection | Live Neutral |
| General Application | Commercial Industrial Educational |
| Operating Temperature Range °C | -10 - +35 |
| Warranty (Years) | 5 |
| Electrical Data | |
| Wattage (W) | 0.5 |
| Mains voltage (V) | 220 - 240 |
| Electrical protection | Class II |
| Driver Output Current (mA) | 2A Max |
| Dimmable | Yes |
| Dimmable Type | Remote Control |
| Nominal Frequency (Hz) | 50/60 |



401752

Sensor Data

| Sensor Technology | PIR |
|-------------------------------|--|
| Sensor Type | Dimmable |
| Max. Mounting Height (M) | 7 |
| Hold Time | 10s/90s/5min/10min/15min/20min/30min/60min |
| Detection area (m) | 2 - 16 (20%/40%/60%/80%/100%/) |
| Detection radius (°) | 360 |
| Wireless Communication | Infrared |
| Remote / APP | Remote |
| Physical Data | |
| Housing colour | White RAL 9003 |
| Body material | ABS |
| IP Rating | 20 |
| Nominal Product Length (mm) | 130 |
| Nominal Product Width (mm) | 36.4 |
| Nominal Product Height (mm) | 28 |
| Weight (kg) | 0.1 |
| Standards and Approvals | |
| Manufactured In Accordance To | EN 60598-1 |
| CE Mark | Yes |
| UKCA Mark | Yes |
| WEEE Symbol | Yes |
| Certificate Of Conformity | Available on Request |
| Accredited Members | LIA, ISO9001 |
| | |