

Emergency

Draycote Emergency Twin Spot 6W 6000K Self Test White

IP20

5 YR  
Warranty

2 YR  
Battery  
Warranty

LiFePO4

6000K



UK  
CA

CE

LiFePO4 battery, Polycarbonate body and diffuser, Non maintained, 20mm conduit entry, Loop in / Loop out terminals



General Data

Technology	LED
Mounting options	Wall
Electrical Connector Type	Push fit terminal
Install Options	20mm Cut Out
Input Cable	0.75-2.5mm²
Input Electrical Connection	Neutral Earth P Live
General Application	Commercial   Industrial   Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

410256

## Technical Specification

## Optical Data

LED Manufacturer / Type	Everlight
Fixture Luminous Flux (Lm)	506
Luminaire Efficacy @6000K (lm/W)	506
LOR %	100
Beam Angle°	100
Photobiological Risk Group	RG0

## Light Source Data

Colour Temperature (K)	6000
Light Colour	Daylight
CRI Ra	70

## Electrical Data

Wattage (W)	6
Total Power Consumption (W)	6
Mains voltage (V)	220 - 240
Lamp power factor	>80
Electrical protection	Class I
Driver Output (V)	12-50
Driver Output Current (mA)	300
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60

## Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	30000
------------------------------	-------

**Emergency Data**

Battery Type	LiFeP04
Battery Capacity (mAh)	6000mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	Self Test
Emergency Duration (Hours)	3
Emergency Output	506

**Physical Data**

Housing colour	White
Body material	Polycarbonate
IP Rating	65
Diffuser Material	Polycarbonate
Nominal Product Length (mm)	280
Nominal Product Width (mm)	90
Nominal Product Height (mm)	301
Weight (kg)	0.66

**Standards and Approvals**

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

410256

## Technical Specification

