

410290-DD

Technical Specification

Amenity

Hurworth Mini Wall Pack 15W 3CCT Black DD



Tough body construction with Polycarbonate diffuser, LED lifespan 30,000 hours L70, Standard, Emergency and Dusk to Dawn options available



General Data

Technology	LED
Mounting options	Surface Mount
Install Options	20mm knock out
Electrical Connector Type	Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	-20 - +40
Warranty (Years)	3

410290-DD

Technical Specification

Optical Data

LED Manufacturer / Type	Epistar
Fixture Luminous Flux (Lm)	1114 1282 1189
Luminaire Efficacy @3000K (lm/W)	74
Luminaire Efficacy @4000K (lm/W)	89
Luminaire Efficacy @6000K (lm/W)	78
LOR %	100
Colour Selectable	Yes
Beam Angle°	105
Photobiological Risk Group	RG0

Light Source Data

Energy Class	F
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	80

410290-DD

Technical Specification

Electrical Data

Wattage (W)	15
Total Power Consumption (W)	15 14.3 15.2
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class II
Driver Output (V)	27-65
Driver Output Current (mA)	260
Control Gear Type CC or CV	Constant Current
SVM	0.04
PstLM	0.01
LED Flicker Rate	1.04
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	<20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

410290-DD

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
------------------------------	-------

Sensor Data

Sensor Technology	Daylight Sensor
-------------------	-----------------

Sensor Type	ON/OFF
-------------	--------

Daylight Threshold	30Lux
--------------------	-------

Physical Data

Housing colour	Black RAL 9005
----------------	----------------

Body material	ABS
---------------	-----

Driver Housing	Polycarbonate
----------------	---------------

IP Rating	65
-----------	----

IK Rating	8
-----------	---

Diffuser Material	Polycarbonate
-------------------	---------------

Diffuser finish	Frosted
-----------------	---------

Nominal Product Length (mm)	275
-----------------------------	-----

Nominal Product Width (mm)	185
----------------------------	-----

Nominal Product Height (mm)	74
-----------------------------	----

Weight (kg)	0.54
-------------	------

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
-------------------------------	------------

CE Mark	Yes
---------	-----

UKCA Mark	Yes
-----------	-----

WEEE Symbol	Yes
-------------	-----

Certificate Of Conformity	Available on Request
---------------------------	----------------------

Accredited Members	LIA, ISO9001
--------------------	--------------

410290-DD

Technical Specification

