

410290-M3-DD

Technical Specification

Amenity

Hurworth Mini Wall Pack 15W 3CCT Black M3 & DD



Tough body construction with Polycarbonate diffuser, LED lifespan 30,000 hours L70, Standard, Emergency and Dusk to Dawn options available



General Data

Technology	LED
Mounting options	Surface Mount
Install Options	20mm knock out
Electrical Connector Type	Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 + 30
Warranty (Years)	3

Optical Data

LED Manufacturer / Type	Epistar
Fixture Luminous Flux (Lm)	1114 1282 1189
Luminaire Efficacy @3000K (lm/W)	74
Luminaire Efficacy @4000K (lm/W)	89
Luminaire Efficacy @6000K (lm/W)	78
LOR %	100
Colour Selectable	Yes
Beam Angle°	105
Photobiological Risk Group	RG0

Light Source Data

Energy Class	F
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	80

410290-M3-DD

Technical Specification

Electrical Data

Wattage (W)	15
Total Power Consumption (W)	15 14.3 15.2
Mains voltage (V)	220 - 240
Lamp power factor	0.9
Electrical protection	Class II
Driver Output (V)	27-65
Driver Output Current (mA)	260
Control Gear Type CC or CV	Constant Current
SVM	0.04
PstLM	0.01
LED Flicker Rate	1.04
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	<20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
------------------------------	-------

Emergency Data

Battery Type	Lumineux
Battery Capacity (mAh)	1500mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3

Sensor Data

Sensor Technology	Daylight Sensor
Sensor Type	ON/OFF
Daylight Threshold	30Lux

410290-M3-DD

Technical Specification

Physical Data

Housing colour	Black RAL 9005
Body material	ABS
Driver Housing	Polycarbonate
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Frosted
Nominal Product Length (mm)	275
Nominal Product Width (mm)	185
Nominal Product Height (mm)	74
Weight (kg)	0.54

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

Product Relations



410290
Hurworth Mini Wall Pack 15W 3CCT Black

410290-M3-DD

Technical Specification



410290-DD
Hurworth Mini Wall Pack 15W 3CCT Black DD



431200
Hurworth Mini Wallpack 12W 3CCT Black IP65



431200-DD
Hurworth Mini Wallpack 12W 3CCT Black IP65 Photocell

