

430019

Technical Specification

Exterior

Lifford Floodlight AC 30W 4000K Black

IP65

110°

3 YR  
Warranty

80  
CRI

4000K

IK08

ATG F



UK  
CA

CE

Diecast Aluminium body, Angled bracket for ease of installation, Supplied with 1m prewired H05RN-F cable, Breather valve to prevent condensation



General Data

Technology	LED
Mounting options	Wall
Install Options	Bracket
Electrical Connector Type	Flying Lead
Input Cable	1M H05RN-F 3-Core
Input Electrical Connection	Live   Neutral   Earth
General Application	Residential   Commercial   Industrial
Operating Temperature Range °C	-20 - +30
Warranty (Years)	3

430019

## Technical Specification

## Optical Data

LED Manufacturer / Type	E Bright
Fixture Luminous Flux (Lm)	3350
Luminaire Efficacy @4000K (lm/W)	110
LOR %	100
Colour Selectable	No
Beam Angle°	110
Photobiological Risk Group	RG0

## Light Source Data

Energy Class	F
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

## Electrical Data

Wattage (W)	30
Total Power Consumption (W)	31.1
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class I
Driver Output (V)	DOB
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	1

430019

## Technical Specification

### Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	30000
------------------------------	-------

### Physical Data

Housing colour	Black RAL 9017
Body material	Diecast Aluminium
IP Rating	65
IK Rating	8
Diffuser Material	Tempered Glass
Diffuser finish	Clear
Nominal Product Length (mm)	165
Nominal Product Width (mm)	180
Nominal Product Height (mm)	32
Weight (kg)	0.56

### Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

430019

## Technical Specification

