

430033-H3

Technical Specification

Linear

Stanford Anti-Corrosive 38W 5000K 4ft Twin Emergency Grey

IP65

5000K

IK08

5 YR
Warranty

50,000
Hours



UK
CA

CE

High efficacy up to 145LPCW, Anti-distortion housing, Improved thermals utilising Aluminium back PCBs, Opal, ribbed Polycarbonate diffuser to reduce glare, Stainless steel clips, H3 – High Output Emergency 440lm option available



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Electrical Connector Type	Screw terminal
Install Options	Fixing Bracket
Input Cable	No
Input Electrical Connection	Live Neutral Earth P Live
General Application	Industrial Commercial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

430033-H3

Technical Specification

Optical Data

LED Manufacturer / Type	Smalite
Fixture Luminous Flux (Lm)	5680
Luminaire Efficacy @5000K (lm/W)	146
LOR %	100
Colour Selectable	No
Beam Angle°	115
Photobiological Risk Group	RG0

Light Source Data

Energy Class	D
Lm/W	146
Colour Temperature (K)	5000
Light Colour	Daylight
CRI Ra	80

430033-H3
Technical Specification
Electrical Data

Wattage (W)	38
Total Power Consumption (W)	38.9
Mains voltage (V)	200 - 240
Lamp power factor	0.95
Electrical protection	Class I
Driver Output (V)	20 - 54
Driver Output Current (mA)	700
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Tridonic
Glow Wire Test (°C)	10
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	2
Max. Luminaire per 10A C Breaker	35
Max. Luminaire per 13A C Breaker	50
Max. Luminaire per 16A C Breaker	65
Max. Luminaire per 20A C Breaker	75
Max. Luminaire per 10A B Breaker	28
Max. Luminaire per 13A B Breaker	40
Max. Luminaire per 16A B Breaker	52
Max. Luminaire per 20A B Breaker	60

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Emergency Data

Battery Type	LiFePO4
Battery Capacity (mAh)	3.6Ah
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours Hours
Emergency Type	Non-Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3
Emergency Output	440

Physical Data

Housing colour	421C Grey
Body material	ABS
Driver Housing	Metal casing
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Milky
Nominal Product Length (mm)	1274
Nominal Product Width (mm)	140
Nominal Product Height (mm)	90
Weight (kg)	2.26

430033-H3

Technical Specification

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

