

430151

Technical Specification

Emergency

Grafham Plug & Play Linear Emergency Pack



Grafham Plug & Play Linear Emergency Pack



General Data

Mounting options	Internal
Electrical Connector Type	Push Terminal
Input Cable	0.75-2.5mm <sup>2</sup>
Input Electrical Connection	Live   Neutral P Live
General Application	Commercial   Industrial   Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

430151

## Technical Specification

## Electrical Data

Wattage (W)	4
Total Power Consumption (W)	4
Mains voltage (V)	220 - 240
Lamp power factor	>80
Electrical protection	Class II
Driver Output (V)	20-60
Driver Output Current (mA)	65-210
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Inrush Current (A)	30
Nominal Frequency (Hz)	50/60

## Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	3600mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Test Procedure	Manual
Emergency Duration (Hours)	3

## Physical Data

Housing colour	White
IP Rating	20
Nominal Product Length (mm)	146
Nominal Product Width (mm)	30
Nominal Product Height (mm)	22.5
Weight (kg)	0.27

430151

Technical Specification

**Standards and Approvals**

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001