

430159-WH


Technical Specification

Amenity

Pebble Utility Round Bulkhead 12W 3CCT White



Tough and Durable body and Polycarbonate Prismatic diffuser, Wall and Ceiling Mount, LED lifespan 50,000 hours L70, Standard, Microwave, Emergency, Dusk to Dawn and 3 step dimming options available, IK08 Impact rated



General Data

Technology	LED
Mounting options	Ceiling Wall
Install Options	BESA 20mm Knock out
Electrical Connector Type	Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Residential Commercial
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

430159-WH

Technical Specification

Optical Data

LED Manufacturer / Type	SMD 2835
Fixture Luminous Flux (Lm)	1252 1324 1313
Luminaire Efficacy @3000K (lm/W)	104
Luminaire Efficacy @4000K (lm/W)	110
Luminaire Efficacy @6000K (lm/W)	109
LOR %	100
Colour Selectable	Yes
Beam Angle°	115
Optics	Symetric
Photobiological Risk Group	RG0

Light Source Data

Energy Class	E
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	>80

430159-WH

Technical Specification

Electrical Data

Wattage (W)	12
Total Power Consumption (W)	11.3 11.0 11.3
Mains voltage (V)	220 - 240
Lamp power factor	>80
Electrical protection	Class I
Driver Output (V)	32-52
Driver Output Current (mA)	280
Control Gear Type CC or CV	Constant Current
SVM	0.02
PstLM	0.01
LED Flicker Rate	0.69
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	<20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

430159-WH
Technical Specification
Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Physical Data

Housing colour	White RAL 9016
-----------------------	----------------

Body material	ABS
----------------------	-----

Driver Housing	Polycarbonate
-----------------------	---------------

IP Rating	66
------------------	----

IK Rating	8
------------------	---

Diffuser Material	Polycarbonate
--------------------------	---------------

Diffuser finish	Frosted
------------------------	---------

Nominal Product Length (mm)	300
------------------------------------	-----

Nominal Product Width (mm)	300
-----------------------------------	-----

Nominal Product Height (mm)	92
------------------------------------	----

Weight (kg)	0.7
--------------------	-----

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
--------------------------------------	------------

CE Mark	Yes
----------------	-----

UKCA Mark	Yes
------------------	-----

WEEE Symbol	Yes
--------------------	-----

Certificate Of Conformity	Available on Request
----------------------------------	----------------------

Accredited Members	LIA, ISO9001
---------------------------	--------------

Product Relations

430159-WH

Technical Specification



430160-WH-MW

Pebley Utility Square Bulkhead 12W 3CCT Microwave White



430160-WH-SD

Pebley Utility Square Bulkhead 12W 3CCT Step Dim White



430160-BL

Pebley Utility Square Bulkhead 12W 3CCT Black



430160-BL-DD

Pebley Utility Square Bulkhead 12W 3CCT Dusk to dawn Black



430160-BL-MW

Pebley Utility Square Bulkhead 12W 3CCT Microwave Black



430160-BL-SD

Pebley Utility Square Bulkhead 12W 3CCT Step Dim Black



430160-WH

Pebley Utility Square Bulkhead 12W 3CCT White



430571

Pebley Utility Square Bulkhead Full Bezel White

430159-WH

Technical Specification



430570
Pebley Utility Square Bulkhead Full Bezel Black



430160-WH-DD
Pebley Utility Square Bulkhead 12W 3CCT Dusk to Dawn White



431126-WH
Pebley Utility Square Bulkhead 12W/16W/18W 3CCT White Plug & Play IP65



431126-BL
Pebley Utility Square Bulkhead 12W/16W/18W 3CCT Black Plug & Play IP65

