


Amenity

Pebble Utility Square Bulkhead 12W 3CCT Dusk to dawn Black



Tough and Durable body and Polycarbonate Prismatic diffuser, Wall and Ceiling Mount, LED lifespan 50,000 hours L70, Standard, Microwave, Emergency, Dusk to Dawn and 3 step dimming options available, IK08 Impact rated



General Data

Technology	LED
Mounting options	Ceiling Wall
Install Options	BESA 20mm Knock out
Electrical Connector Type	Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Residential Commercial
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

Optical Data

LED Manufacturer / Type	SMD 2835
Fixture Luminous Flux (Lm)	1432 1497 1497
Luminaire Efficacy @3000K (lm/W)	119
Luminaire Efficacy @4000K (lm/W)	124
Luminaire Efficacy @6000K (lm/W)	124
LOR %	100
Colour Selectable	Yes
Beam Angle°	115
Optics	Symetric
Photobiological Risk Group	RG0

Light Source Data

Energy Class	E
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	>80

430160-BL-DD

Technical Specification

Electrical Data

Wattage (W)	12
Total Power Consumption (W)	12.8 12.3 12.8
Mains voltage (V)	220 - 240
Lamp power factor	>80
Electrical protection	Class I
Driver Output (V)	35-45
Driver Output Current (mA)	280
Control Gear Type CC or CV	Constant Current
SVM	0.02
PstLM	0.01
LED Flicker Rate	0.69
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	<20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

430160-BL-DD

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
------------------------------	-------

Sensor Data

Sensor Technology	Photocell
-------------------	-----------

Sensor Type	ON/OFF
-------------	--------

Daylight Threshold	30Lux
--------------------	-------

Physical Data

Housing colour	Black RAL 7021
----------------	----------------

Body material	ABS
---------------	-----

Driver Housing	Polycarbonate
----------------	---------------

IP Rating	65
-----------	----

IK Rating	8
-----------	---

Diffuser Material	Polycarbonate
-------------------	---------------

Diffuser finish	Frosted
-----------------	---------

Nominal Product Length (mm)	256
-----------------------------	-----

Nominal Product Width (mm)	256
----------------------------	-----

Nominal Product Height (mm)	90
-----------------------------	----

Weight (kg)	0.7
-------------	-----

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
-------------------------------	------------

CE Mark	Yes
---------	-----

UKCA Mark	Yes
-----------	-----

WEEE Symbol	Yes
-------------	-----

Certificate Of Conformity	Available on Request
---------------------------	----------------------

Accredited Members	LIA, ISO9001
--------------------	--------------

430160-BL-DD

Technical Specification

Product Relations



430159-BL-SD

Pebley Utility Round Bulkhead 12W 3CCT Step Dim Black



430159-WH-SD

Pebley Utility Round Bulkhead 12W 3CCT Step Dim White



430159-BL-DD

Pebley Utility Round Bulkhead 12W 3CCT Dusk to Dawn Black



430159-WH-DD

Pebley Utility Round Bulkhead 12W 3CCT Dusk to dawn White



430159-WH-MW

Pebley Utility Round Bulkhead 12W 3CCT Microwave White



430159-BL-MW

Pebley Utility Round Bulkhead 12W 3CCT Microwave Black



430159-WH

Pebley Utility Round Bulkhead 12W 3CCT White

430160-BL-DD

Technical Specification



430159-BL
Pebley Utility Round Bulkhead 12W 3CCT Black

