

430164

Technical Specification

Emergency

Grafham Bulkhead Emergency Pack



Grafham Bulkhead Emergency Pack

General Data

Mounting options	Internal
Electrical Connector Type	Push Terminal
Input Cable	0.75-2.5mm ²
Input Electrical Connection	Neutral P Live
General Application	Residential Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

Electrical Data

Wattage (W)	2
Total Power Consumption (W)	2
Mains voltage (V)	220 - 240
Electrical protection	Class II
Driver Output (V)	2.5-10
Driver Output Current (mA)	400
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Inrush Current (A)	10
Nominal Frequency (Hz)	50/60

430164

Technical Specification

Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	3600mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Duration (Hours)	3

Physical Data

Housing colour	White
Driver Housing	White
IP Rating	20
Nominal Product Length (mm)	122
Nominal Product Width (mm)	42
Nominal Product Height (mm)	22
Weight (kg)	110

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001