

430202-MW

Technical Specification

Linear

Staunton Anti-Corrosive 56W 4000K 6ft Twin Microwave Grey

IP65

4000K

IK08

5 YR
Warranty

50,000
Hours



UK
CA

CE

Quick release gear tray for faster installation, Threaded 20mm cable entry, Push fit terminals, Stainless steel clips, H3- High Output Emergency 440lm



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Electrical Connector Type	Push fit terminal
Install Options	Fixing Bracket Suspension Bracket
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Industrial Commercial Educational
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

430202-MW

Technical Specification

Optical Data

LED Manufacturer / Type	Shenzen Jingrui
Fixture Luminous Flux (Lm)	7160
Luminaire Efficacy @4000K (lm/W)	128
LOR %	100
Colour Selectable	No
Beam Angle°	120

Light Source Data

Energy Class	E
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

430202-MW
Technical Specification

Electrical Data

Wattage (W)	56
Total Power Consumption (W)	55.2
Mains voltage (V)	220 - 240
Lamp power factor	0.95
Electrical protection	Class I
Driver Output (V)	20 - 54
Driver Output Current (mA)	1050
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Tridonic
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	2
Max. Luminaire per 10A C Breaker	20
Max. Luminaire per 13A C Breaker	30
Max. Luminaire per 16A C Breaker	40
Max. Luminaire per 20A C Breaker	50
Max. Luminaire per 10A B Breaker	16
Max. Luminaire per 13A B Breaker	24
Max. Luminaire per 16A B Breaker	32
Max. Luminaire per 20A B Breaker	40

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Sensor Data

Sensor Technology	Microwave
Sensor Type	ON/OFF
Hold Time	5s 30s 90s 5min 20min 30min
Daylight Threshold	2Lux 10Lux 30Lux 50Lux Disable
Detection radius (°)	150 (Wall mounted) 360 (Ceiling Mounted)

Physical Data

Housing colour	421C Grey
Body material	Polycarbonate
Driver Housing	Metal casing
IP Rating	66
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Frosted
Nominal Product Length (mm)	1840
Nominal Product Width (mm)	100
Nominal Product Height (mm)	80
Weight (kg)	2.5

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001

430202-MW

Technical Specification

