

430209

Technical Specification

Commercial

Eyebrook Lens Downlight UGR 35W 4000K 60° 6" White



Interchangeable reflectors and trims. See accessories, Aluminium heatsink provides excellent thermals, UGR <19High efficiency up to 130Lm/W



General Data

Technology	LED
Mounting options	Ceiling
Install Options	Ceiling
Electrical Connector Type	Flying Lead
Input Cable	2-Core
Input Electrical Connection	Live Neutral
General Application	Commercial Industrial Educational
Minimum Void Requirement (mm)	120
Operating Temperature Range °C	0 - +45
Warranty (Years)	5

430209

Technical Specification

Optical Data

Fixture Luminous Flux (Lm)	3826
Luminaire Efficacy @4000K (lm/W)	111
LOR %	100
Colour Selectable	No
Beam Angle°	60
Photobiological Risk Group	RG0

Light Source Data

Energy Class	E
Lm/W	111
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

430209

Technical Specification

Electrical Data

Wattage (W)	35
Total Power Consumption (W)	34.3
Mains voltage (V)	220 - 240
Lamp power factor	0.9
Electrical protection	Class II
Driver Output (V)	28-40
Driver Output Current (mA)	850
Control Gear Type CC or CV	Constant Current
SVM	0.01
PstLM	0.02
LED Flicker Rate	0.25
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	22
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	1
Max. Luminaire per 10A C Breaker	36
Max. Luminaire per 13A C Breaker	50
Max. Luminaire per 16A C Breaker	63
Max. Luminaire per 20A C Breaker	76
Max. Luminaire per 10A B Breaker	22
Max. Luminaire per 13A B Breaker	30
Max. Luminaire per 16A B Breaker	38
Max. Luminaire per 20A B Breaker	46

430209

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
------------------------------	-------

Physical Data

Housing colour	Black RAL 9005 White RAL 9016
Body material	Aluminium
Driver Housing	ABS
IP Rating	54
IK Rating	8
Zoning Suitability	Zone 2
Diffuser Material	PMMA Plastic
Diffuser finish	Clear Lens
Nominal Product Length (mm)	172
Nominal Product Width (mm)	172
Nominal Product Height (mm)	90
Cut-Out (mm)	150-165
Weight (kg)	0.705


Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN 60598-2-2
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

Product Relations

430209


Technical Specification



430213
Eyebrook 4" Reflector White



430211
Eyebrook 4" Reflector Specular



430545
Eyebrook 4" Reflector Copper




430215
Eyebrook 6" Reflector Black



430216
Eyebrook 6" Reflector White



430212
Eyebrook 4" Reflector Black



430546
Eyebrook 6" Reflector Copper




430214
Eyebrook 6" Reflector Specular

430209

Technical Specification



430259
Eyebrook 6" Reflector Silver



430258
Eyebrook 4" Reflector Silver



430222
Eyebrook 6" Trim Anti-Tamper



430219
Eyebrook 4" Trim Anti-Tamper



430223
Eyebrook 6" Trim Drop Glass



430221
Eyebrook 4" Trim Halo



430224
Eyebrook 6" Trim Halo



430220
Eyebrook 4" Trim Drop Glass

430209

Technical Specification

