

Amenity

Hollingworth Diecast Bulkhead Eyelid 20W 3CCT Microwave Black

IP65

3CCT

BESA



IK10

5 YR
Warranty


50,000
Hours



UK
CA

CE

Tough and Durable Diecast body with Polycarbonate diffuser, Wall and Ceiling Mount, LED lifespan 50,000 hours L70, Standard, Microwave, Emergency, Dusk to Dawn and 3 step dimming options available, IK10 Impact rated



General Data

Technology	LED
Mounting options	Ceiling Wall
Electrical Connector Type	Push Terminal
Install Options	20mm Knock out
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Residential Commercial
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

Optical Data

LED Manufacturer / Type	BMTC 2835
Fixture Luminous Flux (Lm)	1035 1143 1013
Luminaire Efficacy @3000K (lm/W)	54
Luminaire Efficacy @4000K (lm/W)	62
Luminaire Efficacy @6000K (lm/W)	53
LOR %	100
Colour Selectable	Yes
Beam Angle°	110
Optics	Asymmetric
Photobiological Risk Group	RG0

Light Source Data

Energy Class	F
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	>80

430240-MW
Technical Specification
Electrical Data

Wattage (W)	20
Total Power Consumption (W)	19.3 18.4 19.2
Mains voltage (V)	220 - 240
Lamp power factor	>80
Electrical protection	Class I
Driver Output (V)	70-100
Driver Output Current (mA)	175-190
Control Gear Type CC or CV	Constant Current
SVM	0.02
PstLM	0.02
LED Flicker Rate	0.47
Dimmable	No
Driver Brand	Lumineux
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Sensor Data

Sensor Technology	Microwave
Sensor Type	ON/OFF
Max. Mounting Height (M)	6
Hold Time	5s 30s 90s 5min 20min 30min
Detection area (m)	4-6
Daylight Threshold	5Lux 15Lux 30Lux Disable
Detection radius (°)	150 (Wall mounted)/360 (Ceiling mounted)

Physical Data

Housing colour	Black RAL 7021
Body material	Aluminium Die Cast
Driver Housing	Polycarbonate
IP Rating	65
IK Rating	10
Diffuser Material	Polycarbonate
Diffuser finish	Frosted
Nominal Product Length (mm)	365
Nominal Product Width (mm)	365
Nominal Product Height (mm)	105
Weight (kg)	3.8

430240-MW

Technical Specification

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

Product Relations



430239-SD

Hollingworth Diecast Bulkhead Full 20W 3CCT Step Dim Black



430239-DD

Hollingworth Diecast Bulkhead Full 20W 3CCT Dusk to Dawn Black



430239

Hollingworth Diecast Bulkhead Full 20W 3CCT Black



430239-MW

Hollingworth Diecast Bulkhead Full 20W 3CCT - Microwave Black



431129

Hollingworth Diecast Bulkhead 12W/16W/18W 3CCT Black Plug & Play IP65

430240-MW

Technical Specification

