

Emergency

Grafham Plug & Play High Bay Emergency pack









Grafham Plug & Play High Bay Emergency pack



General Data

Mounting options	Internal
Electrical Connector Type	Flying Lead
Input Cable	1.5m H05RN-F 4-Core
Input Electrical Connection	Live Neutral Earth P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5



430264	Technical Specification
Electrical Data	
Wattage (W)	4
Total Power Consumption (W)	4
Mains voltage (V)	220 - 240
Lamp power factor	0.7
Electrical protection	Class I
Driver Output (V)	20-24
Driver Output Current (mA)	150-200
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60
Emergency Data	
Battery Type	LiFeP04
Battery Capacity (mAh)	3600mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3



430264	Technical Specification
Physical Data	
Housing colour	Black RAL 9005
Body material	Aluminium + PC
Driver Housing	Polycarbonate
IP Rating	40
Nominal Product Length (mm)	200
Nominal Product Width (mm)	200
Nominal Product Height (mm)	36
Weight (kg)	0.65
Standards and Approvals	
Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request

LIA, ISO9001

Accredited Members