

430269

Technical Specification

Drivers

Multi Dim Driver (Push Dim, 1-10v & DALI2) 24W - 42W 600-1050mA 30-40VDC



Multi Dim Driver (Push Dim, 1-10v & DALI2) 24W - 42W 600-1050mA 30-40VDC



General Data

Technology	CC AC SELV
Electrical Connector Type	Push Terminal
Input Cable	0.75-2.5mm ²
Input Electrical Connection	Live Neutral
General Application	Commercial Residential Educational
Operating Temperature Range °C	-10 - +40
Warranty (Years)	5

430269

Technical Specification

Electrical Data

Wattage (W)	24 - 45
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class II
Driver Output (V)	30 - 40
Driver Output Current (mA)	600 - 1050
Control Gear Type CC or CV	Constant Current
Dimmable	Yes
Dimmable Type	1-10
Recommended Dimmers	DALI
Inrush Current (A)	16
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	L-N:1
Max. Luminaire per 10A C Breaker	21
Max. Luminaire per 13A C Breaker	35
Max. Luminaire per 16A C Breaker	43
Max. Luminaire per 20A C Breaker	53
Max. Luminaire per 10A B Breaker	21
Max. Luminaire per 13A B Breaker	27
Max. Luminaire per 16A B Breaker	33
Max. Luminaire per 20A B Breaker	41

430269

Technical Specification

Physical Data

Housing colour	White
Body material	ABS
IP Rating	20
Nominal Product Length (mm)	144
Nominal Product Width (mm)	80
Nominal Product Height (mm)	32
Weight (kg)	0.20