

430270

Technical Specification

Drivers

Multi Dim Driver (Push Dim, 1-10v & DALI2) 42W-60W 1050-1500mA 30-40VDC



Multi Dim Driver (Push Dim, 1-10v & DALI2) 42W-60W 1050-1500mA 30-40VDC



General Data

Technology	CC AC SELV
Electrical Connector Type	Push Terminal
Input Cable	0.75-2.5mm²
Input Electrical Connection	Live Neutral
General Application	Commercial Residential Educational
Operating Temperature Range °C	-10 - +40
Warranty (Years)	5

430270
Technical Specification
Electrical Data

Wattage (W)	45 - 60
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class II
Driver Output (V)	30 - 40
Driver Output Current (mA)	1050 - 1500
Control Gear Type CC or CV	Constant Current
Dimmable	Yes
Dimmable Type	1-10
Recommended Dimmers	DALI
Inrush Current (A)	24.2
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	L-N:1
Max. Luminaire per 10A C Breaker	20
Max. Luminaire per 13A C Breaker	25
Max. Luminaire per 16A C Breaker	31
Max. Luminaire per 20A C Breaker	39
Max. Luminaire per 10A B Breaker	19
Max. Luminaire per 13A B Breaker	24
Max. Luminaire per 16A B Breaker	30
Max. Luminaire per 20A B Breaker	38

430270

Technical Specification

Physical Data

Housing colour	White
Body material	ABS
IP Rating	20
Nominal Product Length (mm)	156
Nominal Product Width (mm)	80
Nominal Product Height (mm)	32
Weight (kg)	0.25