

430413-H3

Technical Specification

Linear

Staunton Plus Anti-Corrosive 19W 2CCT 4000K/5000K 4ft Single
Emergency Microwave Grey

Staunton Plus Anti-Corrosive 19W 2CCT 4000K/5000K 4ft Single Emergency Microwave - Grey



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Install Options	Fixing Bracket Suspension Bracket
Electrical Connector Type	Push fit terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth P Live
General Application	Industrial Commercial Educational
Operating Temperature Range °C	0- +30
Warranty (Years)	5

430413-H3

Technical Specification

Optical Data

LED Manufacturer / Type	MTC
Fixture Luminous Flux (Lm)	2940 3060
Luminaire Efficacy @4000K (lm/W)	155
LOR %	100
Colour Selectable	Yes
Beam Angle°	120

Light Source Data

Colour Temperature (K)	4000 5000
Light Colour	Cool White Daylight
CRI Ra	80

430413-H3
Technical Specification
Electrical Data

Wattage (W)	19
Total Power Consumption (W)	19
Mains voltage (V)	100 - 277
Lamp power factor	0.95
Electrical protection	Class I
Driver Output (V)	28 - 42
Driver Output Current (mA)	0.33 - 0.60
Control Gear Type CC or CV	Constant Current
LED Flicker Rate	Flicker-free
Dimmable	No
Driver Brand	Boke
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	2
Max. Luminaire per 10A C Breaker	75
Max. Luminaire per 13A C Breaker	95
Max. Luminaire per 16A C Breaker	120
Max. Luminaire per 20A C Breaker	150
Max. Luminaire per 10A B Breaker	65
Max. Luminaire per 13A B Breaker	90
Max. Luminaire per 16A B Breaker	110
Max. Luminaire per 20A B Breaker	130

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

430413-H3

Technical Specification

Emergency Data

Battery Type	LiFePO4
Battery Capacity (mAh)	3.6Ah
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours Hours
Emergency Type	Non-Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3
Emergency Output	440

Sensor Data

Sensor Technology	Microwave
Sensor Type	ON/OFF
Max. Mounting Height (M)	6
Hold Time	5s 30s 90s 5min 20min 30min
Detection area (m)	10 (4m mounting height)
Daylight Threshold	2Lux 10Lux 30Lux 50Lux Disable
Detection radius (°)	150 (Wall mounted) 360 (Ceiling Mounted)

430413-H3

Technical Specification

Physical Data

Housing colour	421C Grey
Body material	Polycarbonate
Driver Housing	Metal casing
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Frosted
Nominal Product Length (mm)	1240
Nominal Product Width (mm)	100
Nominal Product Height (mm)	80
Weight (kg)	1.5

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001

