

430451-ST

Technical Specification

Emergency

Grafham Universal Emergency Pack - Self test



Grafham Universal Emergency Pack - Self test



General Data

Mounting options	Internal
Electrical Connector Type	Quick connector
Input Cable	0.75-2.5mm <sup>2</sup>
Input Electrical Connection	Live   Neutral   Earth   P Live
General Application	Residential   Commercial   Industrial   Educational
Operating Temperature Range °C	0 - +25
Warranty (Years)	5

430451-ST

## Technical Specification

## Electrical Data

<b>Wattage (W)</b>	3
<b>Mains voltage (V)</b>	220 - 240
<b>Lamp power factor</b>	>80
<b>Electrical protection</b>	Class II
<b>Driver Output (V)</b>	55 VDC
<b>Control Gear Type CC or CV</b>	Constant Current
<b>Driver Brand</b>	Lumineux
<b>Nominal Frequency (Hz)</b>	50/60

## Emergency Data

<b>Battery Type</b>	Li-ion
<b>Battery Capacity (mAh)</b>	5000mAh
<b>Battery Warranty (Years)</b>	2
<b>Recharge Time (Hours)</b>	24 Hours
<b>Test Procedure</b>	Self test
<b>Emergency Duration (Hours)</b>	3

## Physical Data

<b>Housing colour</b>	White
<b>Nominal Product Length (mm)</b>	223
<b>Nominal Product Width (mm)</b>	25
<b>Nominal Product Height (mm)</b>	55
<b>Weight (kg)</b>	0.319

**Standards and Approvals**

Manufactured In Accordance To	EN 60598-1 EN 60598-2
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001