

Sports Lighting

Carsington Plus Sports Light 960W 5000K 25 x 130D



Massive light output of up to 218,000lm, Ultra-High system efficiency over 140lm/WHigh quality Lumileds LED chip and Inventronics driver, Over 50,000 hours lifespan to L70, Professionally designed true asymmetric flat opticsTough IP66 and IK09 constructionHigh quality AkzoNobel anti-corrosion powder coating



General Data

Technology	LED
Mounting options	Pole   Wall
Electrical Connector Type	Flying Lead
Install Options	Mounted on Bracket
Input Cable	1.5m H07RN-F 3-Core
Input Electrical Connection	Yes
General Application	Sports Lighting   Industrial
Operating Temperature Range °C	-30 - +50
Warranty (Years)	5

430511-25

Technical Specification

## Optical Data

LED Manufacturer / Type	Fujian Lightning Optoelectronic
Fixture Luminous Flux (Lm)	132590
Luminaire Efficacy @5000K (lm/W)	135
LOR %	100
Colour Selectable	No
Beam Angle°	25 x 130
Optics	Asymmetric Optic
Photobiological Risk Group	RG1

## Light Source Data

Energy Class	D
Lm/W	135
SDCM	5
Colour Temperature (K)	5000
Light Colour	Daylight
CRI Ra	70

430511-25

## Technical Specification

### Electrical Data

Wattage (W)	960
Total Power Consumption (W)	982
Mains voltage (V)	100 - 277
Lamp power factor	>96
Electrical protection	Class I
Driver Output (V)	108 - 268
Driver Output Current (mA)	2800
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Inventronics
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	20

### Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	102000
Lifespan L80 B20 @25°C (Hrs)	77000
Lifespan L90 B10 @25°C (Hrs)	30000

**Physical Data**

Housing colour	Black RAL 9005
Body material	Aluminium with AkzoNobel anti-corrosive powder coating
Driver Housing	Aluminium Alloy
IP Rating	66
IK Rating	9
EPA Wind Rating	0.066 @ 0°   0.086 @ 10°
Diffuser Material	Polycarbonate
Diffuser finish	Optical Lens
Nominal Product Length (mm)	580
Nominal Product Width (mm)	656
Nominal Product Height (mm)	138
Weight (kg)	21.6

**Standards and Approvals**

Manufactured In Accordance To	EN 60598-1   60598-2-5
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

430511-25

Technical Specification

