

Sports Lighting

Carsington Plus Sports Light 1360W 5000K 25 x 130D

















Massive light output of up to 218,000lm, Ultra-High system efficiency over 140lm/WHigh quality Lumileds LED chip and Inventronics driver, Over 50,000 hours lifespan to L70, Professionally designed true asymmetric flat opticsTough IP66 and IK09 constructionHigh quality AkzoNobel anti-corrosion powder coating



General Data

Technology	LED
Mounting options	Pole Wall
Install Options	Mounted on Brackets
Electrical Connector Type	Flying Lead
Input Cable	1.5m H07RN-F 3-Core
Input Electrical Connection	Yes
General Application	Sports Lighting Industrial
Operating Temperature Range °C	-30 - +50
Warranty (Years)	5



430552-25	Technical Specification
Optical Data	
LED Manufacturer / Type	Lightning
Fixture Luminous Flux (Lm)	182725
Luminaire Efficacy @5000K (Im/W)	135
LOR %	100
Colour Selectable	No
Beam Angle°	25 x 120
Optics	Asymmetric Optic
Photobiological Risk Group	RG1
Light Source Data	
Energy Class	D
Lm/W	135
SDCM	5
Colour Temperature (K)	5000
Light Colour	Daylight
CRI Ra	70



430552-25	Technical Specification
Electrical Data	
Wattage (W)	1360
Total Power Consumption (W)	1353.51
Mains voltage (V)	100 - 277
Lamp power factor	0.96
Electrical protection	Class I
Driver Output (V)	97 - 262
Driver Output Current (mA)	2800
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Inventronics
Inrush Current (A)	1.55
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	20
Lifetime Data	
Lifespan L70 B50 @25°C (Hrs)	102000
Lifespan L80 B20 @25°C (Hrs)	77000
Lifespan L90 B10 @25°C (Hrs)	30000



430552-25	Technical Specification
Physical Data	
Housing colour	Black RAL 9005
Body material	Aluminium with AkzoNobel anti-corrosive powder coating
Driver Housing	Aluminium Alloy
IP Rating	66
IK Rating	9
EPA Wind Rating	0.082 @ 0° 0.102 @ 10°
Diffuser Material	Polycarbonate
Diffuser finish	Optical Lens
Nominal Product Length (mm)	581
Nominal Product Width (mm)	803
Nominal Product Height (mm)	138
Weight (kg)	27.60
Standards and Approvals	
Manufactured In Accordance To	EN 60598-1 60598-2-5
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001



430552-25

Technical Specification





