

Commercial

Avon Air Fire rated Downlight - No Bezel













Avon Air Fire rated Downlight - No Bezel



General Data

Technology	LED
Mounting options	Ceiling
Install Options	Recessed
Electrical Connector Type	Push Terminal
Input Cable	3-Core Ø0.75-2.5mm
Input Electrical Connection	Live Neutral Earth
General Application	Commercial Residential
Minimum Void Requirement (mm)	100
Insulation Coverage	Can be covered
Operating Temperature Range °C	0 - +40
Warranty (Years)	3



430600	Technical Specification
Electrical Data	
Wattage (W)	Max 10W LED
Mains voltage (V)	220 - 240
Electrical protection	Class I
Physical Data	
Housing colour	Black RAL 9005 Housing
Body material	Sheet Metal Plastic
IP Rating	07
Nominal Product Length (mm)	90
Nominal Product Width (mm)	90
Nominal Product Height (mm)	110
Cut-Out (mm)	75
Weight (kg)	0.16
Standards and Approvals	
Manufactured In Accordance To	EN 60598-1 EN 60598-2-2
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001