

Sports Lighting

Wilton FloodLight 240W 5000K Grey 40x130D

















High quality LED chips and driver, Asymmetric Optics, Suitable for swimming pools and coastal areas, 304 stainless steel bracket supplied, Easy installationHigh efficiency up to 140LPCW, IP67 and tough IK09 rated construction



General Data

Technology	LED
Mounting options	Pole Wall
Install Options	Mounted on Bracket
Electrical Connector Type	Flying Lead
Input Cable	1.5m H05RN-F 3-Core
Input Electrical Connection	Live Neutral Earth
General Application	Sports Lighting Industrial
Operating Temperature Range °C	-30 - +40
Warranty (Years)	5



430715 Technical Specification

Optical Data

LED Manufacturer / Type	Lightning / SMD5050
Fixture Luminous Flux (Lm)	35553
Luminaire Efficacy @5000K (Im/W)	150
LOR %	100
Colour Selectable	No
Beam Angle°	40x130
Optics	Asymmetric Optic
Photobiological Risk Group	RG1

Light Source Data

Energy Class	В
Lumens	41067
Colour Temperature (K)	5000
Light Colour	Daylight
CRI Ra	70



430715	Technical Specification
Electrical Data	
Wattage (W)	240
Total Power Consumption (W)	242
Mains voltage (V)	100-277
Lamp power factor	0.97
Electrical protection	Class I
Driver Output (V)	43 - 57
Driver Output Current (mA)	4800
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Inventronics
Inrush Current (A)	5.43
Nominal Frequency (Hz)	50/60
Lifetime Data	
Lifespan L70 B50 @25°C (Hrs)	>60000



30715	Technical Specification
-------	-------------------------

Physical Data

Housing colour	Grey RAL9006
Body material	Die Cast Aluminium
Driver Housing	Aluminium Alloy
IP Rating	67
IK Rating	09
Diffuser Material	Toughened Glass
Nominal Product Length (mm)	487
Nominal Product Width (mm)	385
Nominal Product Height (mm)	94
Cut-Out (mm)	6.92
Weight (kg)	5.06

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001





