

Emergency

Grafham Plug & Play Linear High Bay Emergency Pack



Grafham Plug & Play Linear High Bay Emergency Pack

General Data

| | |
|--------------------------------|---------------------------------------|
| Mounting options | Internal |
| Electrical Connector Type | Flying Lead |
| Input Cable | 1.5m H05RN-F 4-Core |
| Input Electrical Connection | Live Neutral Earth P Live |
| General Application | Commercial Industrial Educational |
| Operating Temperature Range °C | 0 - +30 |
| Warranty (Years) | 5 |

Electrical Data

| | |
|-----------------------------|------------------|
| Wattage (W) | 4.5 |
| Total Power Consumption (W) | 4.5 |
| Mains voltage (V) | 220 - 240 |
| Lamp power factor | >80 |
| Electrical protection | Class I |
| Control Gear Type CC or CV | Constant Current |
| Driver Brand | Lumineux |
| Nominal Frequency (Hz) | 50/60 |

430766

Technical Specification

Emergency Data

| | |
|----------------------------|----------|
| Battery Type | LiFeP04 |
| Battery Capacity (mAh) | 3600mAh |
| Battery Warranty (Years) | 2 |
| Recharge Time (Hours) | 24 Hours |
| Test Procedure | Manual |
| Emergency Duration (Hours) | 3 |

Physical Data

| | |
|----------------|-------|
| Housing colour | Black |
| Body material | ABS |
| IP Rating | 65 |

Standards and Approvals

| | |
|-------------------------------|----------------------|
| Manufactured In Accordance To | EN 60598-1 |
| CE Mark | Yes |
| UKCA Mark | Yes |
| WEEE Symbol | Yes |
| Certificate Of Conformity | Available on Request |
| Accredited Members | LIA, ISO9001 |