

Emergency

Grafham Plug & Play Linear Internal 2W Emergency pack

Grafham Plug & Play Linear Internal 2W Emergency pack



**General Data**

|                                |                                       |
|--------------------------------|---------------------------------------|
| Mounting options               | Internal                              |
| Input Electrical Connection    | Plug & Play                           |
| General Application            | Commercial   Industrial   Educational |
| Operating Temperature Range °C | 0 - +60                               |
| Warranty (Years)               | 5                                     |

**Electrical Data**

|                             |                  |
|-----------------------------|------------------|
| Wattage (W)                 | 2                |
| Total Power Consumption (W) | 2                |
| Mains voltage (V)           | 220 - 240        |
| Electrical protection       | Class II         |
| Driver Output Current (mA)  | <40              |
| Control Gear Type CC or CV  | Constant Current |
| Driver Brand                | Lumineux         |
| Nominal Frequency (Hz)      | 50/60            |

430962

## Technical Specification

## Emergency Data

|                            |                                        |
|----------------------------|----------------------------------------|
| Battery Type               | LiFeP04                                |
| Battery Capacity (mAh)     | 3200                                   |
| Battery Warranty (Years)   | 5                                      |
| Recharge Time (Hours)      | 24 Hours                               |
| Emergency Type             | E-SEI3 - Non maintained and maintained |
| Test Procedure             | Manual and Self Test                   |
| Emergency Duration (Hours) | 3                                      |

## Physical Data

|                             |       |
|-----------------------------|-------|
| Housing colour              | White |
| IP Rating                   | 20    |
| Nominal Product Length (mm) | 170   |
| Nominal Product Width (mm)  | 54    |
| Nominal Product Height (mm) | 32    |
| Weight (kg)                 | 0.23  |

## Standards and Approvals

|                               |                       |
|-------------------------------|-----------------------|
| Manufactured In Accordance To | EN 60598-1 EN 60598-2 |
| CE Mark                       | Yes                   |
| UKCA Mark                     | Yes                   |
| WEEE Symbol                   | Yes                   |
| Certificate Of Conformity     | Available on Request  |
| Accredited Members            | LIA, ISO9001          |