

431310

Technical Specification

Linear

Typhoon Anti-Corrosive 4ft Single 19W 4000K White Plug & Play

IP65

IK08

50,000
Hours

5 YR
Warranty

Flicker
Free

A
T
G
C

UK
CA

CE

160lm/W output performance, Threaded 20mm cable entry, Push fit terminals, Stainless steel clipsHigh output self-test Emergency available



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Install Options	Fixing Bracket Suspension Bracket
Electrical Connector Type	Push fit terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Industrial Commercial Educational
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

431310

Technical Specification

Optical Data

LED Manufacturer / Type	MTC 2835
Fixture Luminous Flux (Lm)	3038
Luminaire Efficacy @4000K (lm/W)	167
LOR %	100
Colour Selectable	No
Beam Angle°	120
Photobiological Risk Group	RG0

Light Source Data

Energy Class	C
Lumens	3324
Lm/W	174
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	>80

431310

Technical Specification

Electrical Data

Wattage (W)	19
Total Power Consumption (W)	19.5
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class I
Driver Output (V)	25-57
Driver Output Current (mA)	350
Control Gear Type CC or CV	Constant Current
SVM	0.01
PstLM	0.01
LED Flicker Rate	0.2
Dimmable	No
Driver Brand	Lifud
Inrush Current (A)	≤14A
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	1
Max. Luminaire per 10A C Breaker	67
Max. Luminaire per 13A C Breaker	84
Max. Luminaire per 16A C Breaker	108
Max. Luminaire per 20A C Breaker	140
Max. Luminaire per 10A B Breaker	40
Max. Luminaire per 13A B Breaker	75
Max. Luminaire per 16A B Breaker	95
Max. Luminaire per 20A B Breaker	110

431310

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
------------------------------	-------

Physical Data

Housing colour	RAL 7038 Grey
Body material	Polycarbonate
Driver Housing	Sheet Steel
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate Frosted Diffuser
Diffuser finish	Frosted
Nominal Product Length (mm)	1240
Nominal Product Width (mm)	100
Nominal Product Height (mm)	84
Weight (kg)	1.25

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

431310

Technical Specification

